

Eaton Corporation  
Innovation Center  
26201 Northwestern Highway  
Southfield, Michigan 48076  
(248) 226-6200

---



May 17, 2010

Mr. Yaroslav Treskov  
c/o Mr. Richard Kuhlman  
Afton Chemical Corporation  
2000 Town Center, Suite 1160  
Southfield, MI 48075

Dear Mr. Treskov

We have reviewed the fluid properties and the 35VQ25 test results on Gazpromneft Hydraulic HLP 32

It is our opinion that Gazpromneft Hydraulic HLP 32 meets the anti-wear requirements for the hydraulic fluid recommendations for Vickers produces according to Brochure 694.

Eaton ATS 373 (ASTM D 6973) 35 VQ25 high pressure vane pump test specifies the test fluid to be ISO viscosity grade 32. You have the option to read across to higher viscosity grade fluid, ISO VG 46 or ISO VG 68, only when the exact same type and percentage of the additive technology is used as in the formulation of ISO 32 fluid.

Sincerely

A handwritten signature in black ink, appearing to read "Thelma Marougy". The signature is fluid and cursive, with a large loop at the end.

Thelma Marougy  
Lubricant Specialist  
Eaton Hydraulics Group

TM/cd

Copy: Eaton: J. LeClair, T. Degler, A. George